

Technical Information


DA748

1 Outline


Title	Change on Main cylinder, Main cylinder complete and Cylinder
Model	DBN600, XNB02 Note: These models are the subject items under Export Trade Control Order of Japan. Provision of the items or technical information is strictly prohibited without specific approval of Japanese government. Do not provide this information to anyone who is not permitted to handle the technical information.
Country	All countries
Description	Grease for the subject parts has been increased for countermeasure against the drop of the driving power on low temperature condition. The only difference is the amount of the grease. See below for the details.

2 Detailed information

Apply Isoflex NB52 (Makita Part No. 042011-9B: 900g) to the entire portions of the following parts. In addition, the following amounts have been added to the specific portions.



The amount has been changed from 1.5g to 2.5g for the inside of Main cylinder/ Main cylinder complete.



The amount has been changed from 1.0g to 2.0g for the outside of Cylinder.

3 Parts information

	Item No.	Current part	Q'ty	I/C	H/S	S/P	New part	Q'ty	Note
[1]	024	MAIN CYLINDER ----- 327028-6	1	Yes	OK	C	MAIN CYLINDER ----- 327028-6	1	
[2]	024	MAIN CYLINDER COMPLETE ----- 144882-1	1	Yes	OK	C	MAIN CYLINDER COMPLETE ----- 144882-1	1	
[3]	030	CYLINDER ----- 327029-4	1	Yes	OK	C	CYLINDER ----- 327029-4	1	

3-1 Marks of Interchangeability (I/C), Handling (H/S), Supplying (S/P)

I/C (Interchangeability)	Yes	The new part can be substituted for the current and the current part can be substituted for the new.
	No	The new part cannot be substituted for the current and the current part cannot be substituted for the new.
	←	The new part can be substituted for the current.
	→	The current part can be substituted for the new.
	S	Interchangeable as a set.
H/S (Handling for plants, agents, and distributors stock of the current parts)	OK	The current parts can be used for the subject item No(s). of the subject model(s).
	NOK	The current parts cannot be used for the subject item No(s). of the subject model(s), but can be used for the other item No(s) or the other models.
	T	The current parts in stock must be thrown away due to the technical reason.
S/P (Supplying the current parts for repair from plants)	L	The plants stop supplying the current parts under the above conditions [Model(s), Countries, Item No(s)]. However, they can supply the current parts under other conditions.
	D	The plants stop supplying the current parts.
	C	The plants continue to supply the current parts.
	Z	The plants continue supplying only for a certain period or amount.
	A	After the current parts in plant stock are cleared, they will be discontinued.

4 Implementation

From serial No. 60136E (April 2021 production)